


# Declaration of performance: Ruukintili Dark Mottled Grey

Nr: YL013/01E


1. Product definition	Category 1 fired brick for indoors and outdoors use
2. Product standard	In walls, columns and partitions according to SFS-EN 771-1:2011+A1:2015
3. Producer	Ylivieskan Tiili Oy, Lentokentäntie 833, 84880 Ylivieska, FINLAND
5. AVCP-procedure	AVCP 2+
6. Harmonized standard	EN 771-1:2011+A1:2015 Approved and audited by Inspecta Sertifiointi Oy (0416) certification nr. <b>0416-CPR-5907-01</b>

## 7. Performance

Water absorption	max 20 %		
Initial rate of water	max 3,5 kg/m <sup>2</sup> /min		
Bond strength	≥ 0,16 N/mm <sup>2</sup> (Weber M5-mortar)		
Reaction to fire	Euro A1		
Frost durability	F2 class (SFS7001/1)		
Product shape	Solid brick	Group 0	
Vapour permeability	5/10 EN 1748		

Dimensions	Nominal dimension			Tolerance T1			Variation R1			Thermal conductivity EN1745; A; P=50%	Compression strength N/mm <sup>2</sup>	Gross dry density kg/m <sup>3</sup> D1 (± 10%)
	Length mm	Width mm	Height mm	L mm ±	W mm ±	H mm ±	L mm ±	W mm ±	H mm ±			
<b>Product code</b>												
MT60	285	85	60	7	4	3	10	6	5	0,34	20	1 490
NT60	270	130	60	6	5	3	10	7	5	0,37	20	1 554
ET60	285	130	60	7	5	3	10	7	5	0,37	20	1 502
SNF	250	120	62	6	4	3	9	7	5	0,34	20	1 480
ARF	250	120	65	6	4	3	9	7	5	0,34	20	1 476
DNF	228	108	54	6	4	3	9	6	4	0,34	20	1 454

The performance of this product is in accordance with the specifications above

  
Ylivieska, 1.6.2020  
Heikki Ryöppy, MD

